

0 35

Standard MANOSKOP® torque wrenches w.permanently installed ratchet

721/30 Quick

Art.No. 50204030 GTIN 4018754268948 Model 721/30 QUICK

Label.	Torque wrench MANOSKOP No. 721/30 Quick Measuring-R. 60-300Nm Output 1/2" L. 553mm
Features.	click-type the measuring element is only under load while force is being applied, no need for manual reset to zero rapid setting thanks to easy-action locking lever in the handle ergonomically designed, non-slip adjuster with a thumb recess dual stop signal twin scales N·m/ft·lb optimised convex handle for strain-free working any force applied to the tool after the 'click' or applied in the opposite direction to the current function – e.g. forcible loosening of a jammed screw - does not act on the trigger mechanism and cannot cause damage to it all the sensitive components are protected by the sturdy tubular steel housing calibration using perfectControl® calibrating unit No 7794 or calibration system No 7706. Readjustment does not require disassembly. certificate in accordance with DIN EN ISO 6789-2:2017 display deviation value ± 4%

Advantages.

Made in Germany – STAHLWILLE release torque wrench, ratchet with punch square, length 553 mm, with calibration certificate (DIN EN ISO 6789-2:2017), 50204030

Lightning-fast and precise torque adjustment

STAHLWILLE: For over 160 years, we as a traditional German company from Wuppertal have stood for tools that are appreciated around the world for their excellent quality Patented, low-wear release system with bending rod

Continued loading after release or loading in the opposite functional direction will not damage the torque wrench

Product highlights.



Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a ¢exible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.

Protected.

The internal mechanism is extremely resistant to mechanical wear and well protected against dirt and soiling inside the outer housing.



Wear-resistant.

Wear resistant trigger system with a flexible rod. In contrast to conventional torque wrenches, it is not necessary to reset the wrench to zero after each job to unload the spring. In this way, users benet from long term accuracy and safe measurement results with less time required.




Fast.


Rapid setting thanks to the easy-action locking lever in the handle. Ergonomically designed, non-slip adjuster with a thumb recess for fast, safe setting of the slider.

Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.

Technical Drawing.





Technical Attributes.

Logistics data.

Output square drive outside 1/2" (inch) Length (IFS) Width (IFS)

555 46

Product data sheet 28.09.2023

b1	28 mm	Height (IFS)	30
b2	44 mm	Length (packed, mm)	580
Width mm (b)	46 mm	Width (packed, mm)	46
Size	30	Height (packed, mm)	45
Height mm (h)	30 mm	Volume (packed, mm)	1.2006 dm3
Height mm (h1)	23 mm	Code	50204030
Height mm (h2)	27,5 mm	Weight (gross, kg)	1,810
Length mm (L)	553 mm	Weight PAP (kg)	0,000
LF	486 mm	Weight PVC (kg)	0,114
Lowest value of measurement range N-m	60 N·m	GTIN	4018754268948
		Country of origin	GERMANY
Measuring range ft-lb	50-220 ft·lb	Region of origin	Nordrhein-Westfalen
Measuring range N-m	60-300 N·m	WEEE/Electrical Act	nicht ear-pflichtig
Nominal value N-m	300 N·m	Customs tariff no.	82041100
Scale division [E1]	10 N·m	Numbers of content units	1
Scale division [E2]	10·lb	per order units	-
		Weight	1646 g

Variants.

Code	Article number (ERP) Article description (Autom)		GTIN
50204005	721/5 QUICK	Torque wrench MANOSKOP No. 721/5 Quick Measuring-R. 6-50Nm Output 3/8" L. 352mm	4018754268917
50204015	721/15 QUICK	Torque wrench MANOSKOP No. 721/15 Quick Measuring-R. 30-150Nm Output 1/2" L. 452mm	4018754268924
50204020	721/20 QUICK	Torque wrench MANOSKOP No. 721/20 Quick Measuring-R. 40-200Nm Output 1/2" L. 483mm	4018754268931
50204030	721/30 QUICK	Torque wrench MANOSKOP No. 721/30 Quick Measuring-R. 60-300Nm Output 1/2" L. 553mm	4018754268948

GTIN-Code.



Spare parts.



59191030 Ratchet spare parts sets for torque wrenches No.721

Images.







STAHLWILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-200 info@stahlwille.de · www.stahlwille.de · Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal