



18V Dual Voltage Rotary Hammer Drill Kit - EY78A1LJ2G57

Feature		<ul style="list-style-type: none"> • Complete concrete plug installation by one tool • Dual function rotary hammer or drill & driver • High speed concrete drilling by air type (Cup piston method) hammer • Slow start switch for accurate drilling with a clean finish • Bit adapter (EY9HX403E) as standard equipment • SDS-plus bit system • LED light to support work • With 2 battery packs, battery charger (EY0L82) and carrying case
Speed at No load (Rotation only)		0-1,250 min-1 (rpm)
Blows Rate per Minute (Rotation with hammering)		0-4,750 bpm
Clutch torque (approx)		1.5-5.4 N.m (1.0 N.m per stage, total 5 stage)
Size (LxHxW) / Weight (including battery pack)		249 mm x 272 mm x 64 mm / 2.60 kg
Battery Pack and Charging time (using EY0L82B)		18V / 4.2Ah (EY9L51B) / Usable:55min. / Full:70min.
Drilling + Fastening Capacity	Concrete Screw - Holes in Concrete and Screws Fastened	ø3.5 mm x 30 mm 200 pcs/charge ø4 mm x 25 mm 200 pcs/charge
	Plastic Anchor Fastening Application - Holes in Concrete and Screws Fastened	ø6 mm x 30 mm 150 pcs/charge ø4.5 mm x 25 mm 150 pcs/charge
Drilling Capacity	Holes in Concrete	ø3.5 mm x 30 mm 250 holes/charge ø10.5 mm x 40 mm 90 holes/charge ø12.5 mm x 40 mm 45 holes/charge ø16.5 mm x 40 mm 15 holes/charge