# GB704

# **PNEUDRAULIC** INSTALLATION TOOL SERIES



44766 Centre Ct. Clinton Twp. MI 48038 USA

(191.7 mm)

+1 586. 226.1500

+1 586. 226.1505




solutions@gagebilt.com



#### **GB704**

Stroke - .540" (13.72 mm) Tool weight - 4.30 lbs. (1.95 kg) Pull load - 3,300 (14.68 kN)



#### **GB704SH**

Stroke - .600" (15.24 mm) Hand held weight - 2.00 lbs. (.91 kg) Entire tool weight - 7.25 lbs. (3.29 kg) Pull load - 3,300 (14.68 kN)

Standard Hyd. Hose Length - 8ft (2.4m)

5ft Hyd. Hoses are recommended with use of Backpack Additional custom lengths are available.



5ft Hvd. Hoses are recommended with use of Backpack Additional custom lengths are available.

The GB704 series are pneumatic-hydraulic installation tools, designed specifically for the efficient installation of blind rivets. They can be operated in any position and have a rated pull load of 3,300 (14.68 kN) pounds with 90 psi (6.2 bar) air pressure at the air inlet.

The GB704SH and GB704SR split handle installation tools offer a unique "split" system providing the operator with an ergonomic tool with reduced hand held weight. The GB704SH comes with 8 feet (2.4 m) of hose and the GB704SR comes with 3 feet (.91 m) of hose. Use with our "NEW" Split-System Backpacks to increase user mobility, ergonomics and productivity. Contact GAGE BILT for more information.

The GB704 series tools operate on 90 to 100 psi. (6.2-6.9 bar) of air pressure, with 90 psi. (6.2 bar) providing the maximum efficiency. At 90 psi. (6.2 bar) of air pressure, the GB704 series does not exceed 81.5 dB(A) and consumes .16 SCF/cycle (4.53 L/cycle). The air inlet is provided with 1/4-18 female pipe thread to accept the users air hose fitting.

> NOSE ASSEMBLIES ARE NOT FURNISHED WITH TOOL AND MUST BE ORDERED SEPARATELY





#### **GB704 ACCESSORIES**





**OFFSET** 

#### **NOSE ASSEMBLY CHART**

(Sold Separately)

#### **ACCESSORIES** (Sold Separately)

#### Catcher Bag-Stem #704214





#### Air Bleeder Assy #704153

(Sold Separately)



### Grip Gage #GB105093

For NAS LOCKBOLTS and blind fasteners (Sold Separately)



### Grip Gage #269G3

For CHERRYMAX® and CHERRYLOCK® rivets (Sold Separately)





## **STRAIGHT** (Sold Separately) (Sold Separately) (Sold Separately)

RIGHT ANGLE

FASTENER	DIAMETER	STRAIGHT	RIGHT ANGLE (2)	OFFSET
CHERRYMAX®, CHERRYMAX® 'AB', MBC® LOCK CREATOR BACR15FR/FP, BACR15GF/GK	1/8	456MAX-701-17 (1)	456MAX-704-54RA (1)	456MAX-704-43OS (1)
	5/32	456MAX-704-35 (1)		
	3/16	456MAX-749-35 (3, 1)		
NUT PLATE RIVETS MS20600 SERIES CCR244/264/274 MS/9SP/PT BACR15CC/CF/DA/DR	3/32	3C-704A-16	3C-704-54RA	3C-704A-40OS
	1/8	4C-704A-16	4C-704-54RA	4C-704A-40OS
	5/32	5C-704A-16	5C-704-54RA	5C-704A-40OS
	3/16	6C-704A-16	6C-704-54RA	6C-704A-40OS
'A' CODE NAS1398A NAS1399A	3/32	3A-704A-16	3A-704-54RA	3A-704A-40OS
	1/8	4A-704A-16	4A-704-54RA	4A-704A-40OS
	5/32	5A-704A-16	5A-704-54RA	5A-704A-40OS
	3/16	6A-704A-16	6A-704-54RA	6A-704A-40OS
GROUND STUD M83454 BACS53B1EA1/2	8/32 10/32	GS8-704-16 GS10-704A-19	GS8-704A-54RA GS10-704-54RA	GS8-704-40OS GS10-704A-40OS

CHERRYMAX® and MBC® are registered trademarks of Cherry Aerospace Fasteners.

#### GAGE BILT CERTIFIES THE GB704 WILL INSTALL THE ABOVE FASTENERS

1) INSTALLS 1/8", 5/32", AND 3/16" DIAMETERS

2) RIGHT ANGLE NOSE ASSEMBLIES MAY REQUIRE MORE THAN ONE PULL

3) FRONT END EJECTING NOSE ASSEMBLY.

NOTE: THE LAST 2 DIGITS OF THE NOSE ASSEMBLY REPRESENTS THE LENGTH THE NOSE EXTENDS FROM THE TOOL I.E. -20 = 2.0 INCHES 8/18

