Desoldering tool for lead-free soldering





*Nozzle is an optional part.



Excellent thermal recovery

The integrated nozzle contains both heater and sensor to provide more powerful thermal recovery than conventional tips.

Thermal Recovery Graph Temp (°C) 450 Approx. 30 sec. (Approx. 100	
400-	
350-	- WHAT HAN HALF MANY
300-	
250-	104 sec
200 -	
150-	
	Idered points (using lead-free solder)
	I move to the next point one by one when the temperature
50 reaches to	200°C.
50 100 15	200 250 300 350 Time (sec.)

Easy maintenance

- •Uses disposable paper filter pipes. Allows paper and solder to be disposed of separately.
- Quick nozzle replacement. Nozzle can be replaced safely with the provided nozzle remover.

Safe design

Equipped with a nozzle lock function. Inserting a nozzle into the grip automatically locks it in place and prevents the nozzle cartridge from being pulled out suddenly.

Sleep function

After the iron is inserted into the iron holder, the sleep function activates after a user-settable time (0 to 29 min.) and the tip temperature will decrease to approximately 200°C.

Auto power shut-off function

After 30 minutes have elapsed after inserting the iron into the iron holder, the auto power shut-off function activates and stops to apply power to the heating element.

*It is necessary to change unit settings before using sleep and auto power shut-off functions.

Selectable grip

Detachable handle allows two-way use: gun type or straight type.



When the gun grip is attached When the gun grip is detached







HAKOFM-204

Specifications

• HAKKO FM-204

• HAILING I WI 204	
Power Consumption	120W
Temperature Range	200 to 450°C
Temperature Accuracy	±5°C at idle temperature

Station

Output	24V
Dimensions	160(W) x 120(H) x 225(D)mm
Weight	3.7kg
Vacuum Generator	Vacuum pump, double cylinder type
Vacuum Pressure (Max.)	80kPa (600mmHg)
Suction Flow	15L/min

MODEL FM-2024 Desoldering Tool

Power Consumption	70W (24V)
Temperature Range	350 to 450°C
Tip to Ground Resistance	< 2Ω
Tip to Ground Potential	< 2mV
Total length (w/o Cord)	180mm with ø1.0 nozzle
Weight (w/o Cord & Hose)	65g with ø1.0 nozzle
Cord	1.2m
	1.2m

The temperature was measured using the HAKKO FG-101 thermometer.



Packing List



HEAD OFFICE

HAKKO CORPORATION **OVERSEAS AFFILIATES**

U.S.A. AMERICAN HAKKO PRODUCTS, INC. 28920 N. AVE. WILLIAMS VALENCIA, CA 91355, U.S.A. TEL: (661) 294-0090 FAX: (661) 294-0096 Toll Free (800)88-HAKKO http://www.hakkouscom

4-5, SHIOKUSA 2-CHOME, NANIWA-KU, OSAKA, 556-0024 JAPAN TEL:+81-6-6561-3225 FAX:+81-6-6561-8466 http://www.hakko.com E-mail:sales@hakko.com

HONG KONG HAKKO DEVELOPMENT CO., LTD. ROOM 1504, EASTERN HARBOUR CENTRE, 28 HOI CHAK STREET, QUARRY BAY, HONG KONG. TEL: 2811-5588 FAX: 2590-0217 http://www.hakko.com.hk E-mail:info@hakko.com.hk

Increase your options

The FM-204 is a desoldering station as standard, but it can be operated with optional FM-2027 and FM-2026 soldering handpieces. A single station plays multiple roles: soldering and desoldering.





HAKKO FM-2027

*Fur further details, refer to the N2 system brochure.

Replacement and Optional Parts


Part No.	Name/Description
A1514	Ceramic paper filter/10pcs
A1512	Front holder
A1511	Filter pipe assembly
B3253	Connecting cable
FM2027-03*	HAKKO FM-2027 Conversion kit
FM2026-06*	HAKKO FM-2026 Conversion kit
*Iron holder (No.FH200-01) is included.	

1) (N

Replacement Nozzle

10.7

SINGAPORE HAKKO PRODUCTS PTE., LTD. 1, GENTING LINK #02-04, PERFECT INDUSTRIAL BUILDING, SINGAPORE 349518 TEL: 6748-2277 FAX: 6744-0033 http://www.hakko.com.sg E-mail:sales@hakko.com.sg



1<u>6.7</u>

CA00289BbBa002 Dec. 2007

Please access to the following for the other Sales affiliates. http://www.hakko.com